

2020 OUTLANDER™ MAX 6x6 DPS™ 650

HIGHLIGHTS

- Rotax® V-twin engine
- New arched double A-arm front suspension with front sway bar
- Continuously Variable Transmission (CVT) with Extra-Low L Gear
- 700-lb (318 kg) capacity Dual-Level™ cargo box with modular accessories
- 1,650-lb (750 kg) towing capacity
- Tri-Mode Dynamic Power Steering (DPS)
- Double Torsional Trailing arm Independent (TTI2) rear suspension
- 12-in. cast-aluminum wheels
- Relocated air intakes
- Quick release rear sway bar
- High-strength, multifunction racks with LinQ™ quick-attach accessory system
- RF Digitally Encoded Security System (D.E.S.S.™)



Green / 650

ENGINE	650
Type	62 hp, Rotax 649.6 cc V-twin, liquid cooled
Fuel Delivery System	Electronic Fuel Injection (EFI)
Transmission	CVT, P / R / N / H / Extra-Low L, standard engine braking
Drive Train	Selectable 4WD / 6WD with Visco-Lok® QE auto-locking front differential
Power Steering	Tri-Mode Dynamic Power Steering (DPS)

SUSPENSIONS

Front Suspension	Arched double A-arm with front sway bar 9.2 in. (23.3 cm) travel
Front Shocks	Oil
Rear Suspension	Double Torsional Trailing arm Independent (TTI2) with quick-release sway bar 9.9 in. (25.1 cm) travel
Rear Shocks	Oil

BRAKES

Front	Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers
Rear	Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers

FEATURES

Gauge	Multifunction digital: Speedometer, tachometer (bar graph RPM, bottom bar numerical RPM), odometer, trip & hour meters, diagnostic center, gear position, engine hour meter, 4 x 4 indicator, temperature and engine lights, fuel gauge, clock	Instrumentation	Lighter type DC outlet in console, standard connector in the back (15-A)
Winch	Prewired for available winch	Lighting	230 W from twin 60-W projectors and dual 55-W reflectors with tail light / brake light
Protection	Central skid plate	Seat	Convertible Rack System (CRS)
		Anti-theft System	RF Digitally Encoded Security System (D.E.S.S.)

WARRANTY

Factory	6-months limited warranty
Extended	Up to 36 months B.E.S.T. coverage

TIRES / WHEELS

Front Tires	Carlisle® ACT radial 26 x 8 x 12 in. (66 x 20.3 x 30.5 cm)
Rear Tires	Carlisle ACT radial 26 x 10 x 12 in (66 x 25.4 x 30.5 cm)
Wheels	12-in. cast-aluminum

DIMENSIONS / CAPACITIES

L x W x H	124.8 x 48.5 x 55.3 in. (317 x 123 x 140 cm)
Wheelbase	90 in. (228.5cm)
Ground Clearance	11 in. (27.9 cm)
Seat Height	34.5 in. (87.7 cm)
Dry Weight*	1100 lb (499 kg)
Rack Capacity	Front: 100 lb (45 kg) Rear: 700 lb (318 kg)
Storage Capacity	Dual-level cargo box with sidewalls and tailgate Rear: 18.5 gal (70 L)
Towing Capacity	1,650 lb (750 kg)
Fuel Capacity	5.4 gal (20.5 L)

BEST PROTECTION ©2019 Bombardier Recreational Products Inc. (BRP). All rights reserved.™, ® and the BRP logo are registered trademarks of BRP or its affiliates. Products are distributed in the U.S.A. by BRP US Inc. *Base model dry weight shown. †Visco-Lok is a trademark of GKN Viscodrive GmbH. All other trademarks are the property of their respective owners. Because of our ongoing commitment to product quality and innovation, BRP reserves the right at anytime to discontinue or change specifications, price, design, features, models or equipment without incurring any obligation. Ride responsibly. BRP highly recommends that all ATV drivers take a training course. For safety and training information, see your dealer or, in U.S.A. call the ATV Safety Institute at 1 (800) 887-2887. In Canada, call the Canadian Safety Council at 1 (613) 739-1535 ext 227. ATVs can be hazardous to operate. For your safety: the operator and passenger should wear a helmet, eye protection and other protective clothing. Always remember that riding and alcohol / drugs don't mix. Never ride on paved surfaces or public roads. Never engage in stunt driving. Avoid excessive speeds and be particularly careful on difficult terrain. ATVs with engine sizes of greater than 90cc are recommended for use only by those age 16 and older. Never carry passengers on any ATV not specifically designated for such use.

can-am.



Can-AmOffroad.com